



TECHNICAL DATA SHEET

0W-30 ECO LS FD

Fully synthetic low SAPS engine oil

Product code: U229

Product Description:

0W-30 ECO LS FD is a fully synthetic low SAPS engine oil and provides full compatibility with after-treatment systems such as diesel particulate filters and three-way catalytic converters. It demonstrates a high degree of tolerance towards biodiesel contamination which is known to compromise the oxidation resistance of the engine lubricant.

Benefits:

- Fuel saving technology
- Compatibility with after treatment systems
- Fully synthetic, long drain formulation
- Very high standards of engine cleanliness
- Exceptional anti-wear performance
- Tolerant of biodiesel contamination

Application:

0W-30 ECO LS FD has been developed primarily for modern Ford vehicles requiring the WSS-M2C950-A specification. In addition, this product is recommended for applications requiring an ACEA C2, SAE 0W-30 specification making it suitable for a variety of models from manufacturers including Toyota, Honda and Kia.

Product Specification:

ACEA	C2
Ford	WSS-M2C950-A
JAGUAR LAND ROVER	STJLR.03.5007

Typical Test Data:

Density @ 15°C	0.841
Kinematic Viscosity @ 100°C (cSt)	9.3
Kinematic Viscosity @ 40°C (cSt)	43.7
Viscosity Index	203
Pour Point (°C)	-50
Sulphated Ash (% wt)	0.79
Flash Point COC (°C)	216

Health & Safety:

Please refer to the health and safety data sheet, a copy of which is freely available to all of our customers.