



TECHNICAL DATA SHEET

10W-60 HP FS

Fully Synthetic Engine Oil

Product code: U244

Product Description:

EXOPRO 10W-60 HP FS is manufactured from fully synthetic base stocks and the latest additive technology available, providing a lubricant with outstanding performance and durability for the most demanding motorist. Its optimised viscosity grade allows it to cope with the high operating temperatures encountered in high performance engines and its highly shear stable additive chemistry provides stay-in-grade characteristics for extended periods.

Benefits:

- High film strength provides superior engine protection
- Low volatility greatly reduces oil consumption
- Excellent anti-wear protection
- Highly shear stable
- Outstanding thermal stability at elevated temperatures

Applications:

EXOPRO 10W-60 HP FS is suitable for normally aspirated and turbocharged petrol and diesel engines, especially high powered engines running at elevated temperatures. It is recommended for use in BMW M series models requiring a SAE 10W-60 viscosity grade.

Product Specification:

ACEA	A3/B3, A3/B4
API	SN/CF

Typical Test Data:

Specific Gravity @ 15.6°C	0.859
Kinematic Viscosity @ 100°C (cSt)	22.61
Kinematic Viscosity @ 40°C (cSt)	153.1
Viscosity Index	176
Flash Point COC (°C)	225
Pour Point (°C)	-39
TBN (mg KOH / g)	10.20

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.