



TECHNICAL DATA SHEET

15W-40 PREMIUM

Mineral oil based engine oil

Product code: U202

Product Description:

High performance multigrade engine oil with multifleet applications. Present day motor engineering and motoring conditions have necessitated the rapid advancement in lubricant design and performance. 15W-40 Premium is a new generation multigrade engine oil manufactured from carefully selected base oils and the very latest additive technology. It meets the majority of the latest engine builder requirements and specifications. It can be confidently supplied for most mixed fleet applications. Superior dispersant additives help maintain engine cleanliness in the latest petrol engines and the latest detergent additives help reduce unwanted deposits in turbochargers and on pistons.

Benefits:

- Excellent high temperature stability
- Blended with the latest additive technology
- Excellent sludge control for stop-go city motoring
- Provides ultimate engine protection for all driving conditions

Applications:

15W-40 Premium is suitable for normally aspirated and turbocharged highly stressed petrol engines and diesel engines in the passenger cars and heavy commercials, vans, plant, buses and industrial equipment. It is miscible with all synthetic and mineral based engine oils.

Product Specification:

API	SL/CH-4
ACEA	A3/B3, A3/B4, E2
VW	505.00
MB	228.1, 229.1
Mack	EO-L
MAN	271
MTU	Type 1
Volvo	VDS



TECHNICAL DATA SHEET

Typical Test Data:

Specific Gravity @ 15.6°C	0.886
Kinematic Viscosity @ 100°C (cSt)	14.25
Kinematic Viscosity @ 40°C (cSt)	104.9
Viscosity Index	139
Flash Point COC (°C)	215
Pour Point (°C)	-30
TBN (mg KOH / g)	10.2

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.