



TECHNICAL DATA SHEET

5W-30 SS PREMIUM

Semi-synthetic passenger car engine oil

Product code: U212

Product Description:

5W-30 SS Premium is a semi-synthetic, fuel efficient multigrade engine oil suitable for use in a wide range of passenger cars and vans.

Engine design has changed rapidly over recent years. Increased output from smaller units coupled with reduced engine oil sump capacity has led to greater demands on the lubricant.

5W-30 SS Premium is manufactured from a balanced blend of top quality mineral and synthetic base stocks combined with high performance additives to produce an engine oil which provides outstanding levels of protection. Its naturally higher lubricity offers lower internal friction for reduced engine wear. Its low viscosity offers improved flow rates during cold start and engine idling, a problem with many higher viscosity oils. Premium Semi Synthetic 5W-30 offers excellent stay in grade performance for today's modern multi-valve engines.

Benefits:

- Recommended for use in pre-2009 Ford engines
- Extended drain capability
- Excellent low temperature stability for improved flow rates
- Improved fuel efficiency
- Semi-synthetic formulation

Applications:

5W-30 SS Premium is suitable for normally aspirated and turbocharged highly stressed diesel and petrol engines in passenger cars and light commercials. It is miscible with all synthetic and mineral based engine oils.

Product Specification:

API	SL/SJ/CF
ACEA	A1/B1
FORD	WSS-M2C-913-B & A
BMW	LL-FE-01
OPEL	Pass
ILSAC	GF-2



**TECHNICAL
DATA
SHEET**

Typical Test Data:

Specific Gravity @ 15.6°C	0.875
Kinematic Viscosity @ 100°C (cSt)	11.40
Kinematic Viscosity @ 40°C (cSt)	69.02
Viscosity Index	159
Flash Point COC (°C)	225
Pour Point (°C)	-38
Total Base Number (mg KOH / g)	8.89

Health & Safety:

Please refer to the health and safety data sheet, a copy of which is freely available to all of our customers.