



TECHNICAL DATA SHEET

5W-30 C2, C3 LS

Fully synthetic low SAPS engine oil

Product code: U230

Product Description:

5W-30 C2, C3 LS is a fully synthetic multigrade engine oil formulated from hydrocracked synthetic base stocks, an advanced detergent-dispersant additive package, and shear stable polymers.

The low SAPS (sulphated ash, phosphorus and sulphur) formulation of 5W-30 C2, C3 LS ensures compatibility with exhaust after treatment systems, such as particulate filters and catalytic converters.

Benefits:

- Cost-effective coverage for a wide range of vehicles
- Exhaust after treatment system compatible
- Promotes reduced fuel consumption
- Ensures maximum engine protection
- Excellent high and low temperature stability

Applications:

5W-30 C2, C3 LS is recommended for use in a wide variety of passenger cars and vans with petrol and diesel engines, including those that require a low SAPS oil with the following performance requirements.

Product Specification:

ACEA	C2, C3
API	SN/CF

Typical Test Data:

Density @ 15°C	0.855
Kinematic Viscosity @ 100°C (cSt)	12.0
Kinematic Viscosity @ 40°C (cSt)	72.7
Viscosity Index	162
Flash Point, COC (°C)	230
TBN (mg KOH/g)	7.1