



TECHNICAL DATA SHEET

5W-40 PREMIUM

Fully synthetic passenger car engine oil

Product code: U234

Product Description:

5W-40 Premium is manufactured from fully synthetic base stocks and the latest additive technology available, providing a lubricant with outstanding performance and durability for the most demanding motorist. It offers quicker oil circulation for improved cold starting properties and higher lubricity for reduced internal friction compared with standard mineral based engine oils.

Benefits:

- Excellent high temperature stability
- Suitable for a wide range of vehicles
- Provides ultimate engine protection for all driving conditions
- Not to be used in vehicles with diesel particulate filters

Applications:

5W-40 Premium is suitable for normally aspirated and turbocharged petrol and diesel engines in passenger cars and light commercials and is suitable for all driving conditions. It is miscible with all synthetic and mineral based engine oils.

Product Specification:

API	SN/CF
ACEA	A3/B3, A3/B4
VW	502.00, 505.00, 501.01
MB	229.5, 229.3
GM	LL-B-025
BMW	LL-01
Renault	RN0700, RN0710
PSA	B71 2296
Porsche	A40



TECHNICAL DATA SHEET

Typical Test Data:

Specific Gravity @ 15.6°C	0.849
Kinematic Viscosity @ 100°C (cSt)	14.7
Kinematic Viscosity @ 40°C (cSt)	93.0
Viscosity Index	165
Flash Point COC (°C)	223
Pour Point (°C)	-36
TBN (mg KOH / g)	10.2

Health & Safety:

Please refer to the health and safety data sheet, a copy of which is freely available to all of our customers.