



TECHNICAL DATA SHEET

0W-30 ECO LS FE

Fully synthetic low SAPS engine oil

Product code: U240

Product Description:

0W-30 ECO LS FE is a new generation, fully synthetic multigrade engine oil formulated using the latest developments in synthetic technology together with the most up to date additive chemistry. The optimised viscosity allows significant fuel economy benefits to be achieved, thus minimising environmental impact, while maintaining very high levels of engine protection.

Benefits:

- Effective environmental protection
- Significant reduction in fuel consumption
- Very high standards of engine cleanliness
- Exceptional long term anti-wear and oxidation stability

Application:

0W-30 ECO LS FE is particularly suited to vehicles equipped with anti-pollution systems such as diesel particulate filters where the product's low SAPS levels will greatly prolong the filter's lifespan. These same features also ensure the maximum performance of catalytic converters since phosphorus and sulphur can impair the operation of such devices. This offers further environmental advantages by ensuring efficient treatment of exhaust gases.

Product Specification:

ACEA	C2
API	SM/CF

Typical Test Data:

Density @ 15°C	0.846
Kinematic Viscosity @ 100°C (cSt)	9.7
Kinematic Viscosity @ 40°C (cSt)	52.5
Viscosity Index	173
Pour Point (°C)	-46
Sulphated Ash (% wt)	0.78
Flash Point COC (°C)	215

Health & Safety:

Please refer to the health and safety data sheet, a copy of which is freely available to all of our customers.