



TECHNICAL DATA SHEET

75W-90 SS GL4 & GL5

Semi synthetic based GL-5 & GL-4 gear oil

Product code: U301

Product Description:

EXOPRO 75W-90 SS is new generation of extreme pressure, semi-synthetic, multigrade gear oil meeting the API performance levels GL-4 and GL-5.

EXOPRO 75W-90 SS gear oil is manufactured from high quality synthetic hydrocarbon base stocks which have a high viscosity index and a combination of mineral oils and extreme pressure (EP) additives to provide a lubricant with outstanding anti wear protection. It is designed to cope with the increasing demands of modern motoring conditions, which include high shock load, high torque and high speed service conditions.

Benefits:

- Excellent oxidation stability
- Outstanding low and high temperature performance
- May be used where an SAE 80W-90, 85W-90 or 90 API GL-4 or GL-5 oil is specified.
- Good protection against rust and corrosion
- Very high level of wear protection
- Suitable for use in most synchromesh gearboxes and hypoid axle units
- Improved fuel economy

Applications:

EXOPRO 75W-90 SS GL5 is suitable for the majority of manual gearboxes, including hypoid gears, synchromesh gearboxes and final drives fitted to automotive and commercial vehicles.

Product Specification:

API	GL-4, GL-5
Military	Mil-L-2105D



**TECHNICAL
DATA
SHEET**

Typical Test Data:

Density @ 20°C	0.865
Kinematic Viscosity @ 40°C (cSt)	94.0
Kinematic Viscosity @ 100°C (cSt)	14.5
Viscosity Index	160
Brookfield Viscosity @ -40°C (cP)	126,000
Flash Point COC (°C)	220

Health & Safety:

Please refer to the health and safety data sheet, a copy of which is freely available to all of our customers.