



TECHNICAL DATA SHEET

75W-90 FS

Fully synthetic based GL-4 & GL-5 gear oil

Product code: U304

Product Description:

EXOPRO 75W-90 FS is a fully synthetic, heavy duty, multipurpose automotive gear oil meeting the API requirements GL-4 & GL-5. EXOPRO 75W-90 FS is manufactured from high quality synthetic hydrocarbon base stocks with a high viscosity index and a combination of performance additives, which provide a gear lubricant designed for modern motoring conditions. It demonstrates outstanding load carrying capacity, which is essential for shock load, high torque and high speed service operation.

Benefits:

- Increased fuel economy
- May be used where an 80W-90, 85W-90 or 90 API GL-4 or GL-5 oil is specified.
- Outstanding oxidation stability and resistance to thermal breakdown
- Very high levels of wear protection
- Smoother gear change
- Synthetic formulation provides excellent low temperature characteristics and long fluid life

Application:

EXOPRO 75W-90 FS is recommended for highly stressed manual gearboxes, including synchromesh, in cars, vans, trucks, buses, agricultural, construction and industrial equipment.

Product Specification:

API	GL-4, GL-5
Military	Mil-L-2105D
ZF	TE-ML 07A, 08

Typical Test Data:

Density @ 20°C	0.868
Kinematic Viscosity @ 40°C (cSt)	105.8
Kinematic Viscosity @ 100°C (cSt)	15.5
Viscosity Index	155
Brookfield Viscosity @ -40°C (cP)	137,700
Flash Point COC (°C)	220

Health & Safety:

Please refer to the health and safety data sheet, a copy of which is freely available to all of our customers.