



## TECHNICAL DATA SHEET

# HD 85W-140

Mineral oil based GL-5 gear oils

Product code: U308

### Product Description:

HD 85W-140 is a universal extreme pressure gear oils meeting the API performance levels GL-4 & GL-5. HD 85W-140 gear oil is manufactured from high quality base oils and high levels of extreme pressure (EP) additives to provide a lubricant with outstanding anti wear protection. Designed to cope with the increasing demands of today's motoring conditions, which include high shock/load, high torque, and high speed service conditions.

### Benefits:

- Excellent oxidation stability
- Outstanding low and high temperature performance
- Suitable for synchromesh gearboxes
- Long service life
- Good protection against rust and corrosion
- High level of wear protection

### Application:

HD 85W-140 gear oil is suitable for manual gearboxes, including synchromesh, fitted to automotive vehicles, industrial and commercial vehicles.

### Product Specification:

API	GL-5, GL-4
Military	Mil-L-2105D

### Typical Test Data:

Specific Gravity @ 15.6°C	0.898
Kinematic Viscosity @ 100°C (cSt)	26.39
Kinematic Viscosity @ 40°C (cSt)	320.1
Viscosity Index	109
Flash Point, COC (°C)	245
Pour Point (°C)	-17

### Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.