



TECHNICAL DATA SHEET

75W-80 EPZ FS

Fully synthetic commercial vehicle gear oil

Product code: U309

Product Description:

75W-80 EPZ FS is a new fully synthetic gear oil designed for use in a wide variety of commercial vehicle manual transmissions. It provides extended oil drain performance and excellent component protection even under arduous conditions.

Benefits:

- Very long service life
- Excellent oxidative and thermal stability
- Outstanding low and high temperature performance
- Excellent gear and bearing pitting resistance
- High level of wear protection
- Compatible with a variety of synchroniser materials
- Fuel saving benefits

Application:

75W-80 EPZ FS is recommended for use in all types of ZF manual and automated manual transmissions fitted to commercial vehicles. This includes AS Tronic, eTronic, Ecosplit, Ecomid and Ecolite units which makes 75W-80 EPZ FS an ideal choice for use in DAF, Iveco, MAN and Renault trucks which employ these systems.

In addition, 75W-80 EPZ FS is recommended for use in commercial vehicle transmissions where any of the following specifications are required. This further broadens its scope of application to many models of Volvo, Mercedes and others.

Product Specification:

ZF	TE-ML 01L, 02L, 08, 16K TE-ML 02A, 02B, 02D, 02E
MAN	341 Type Z-4, Z-3, Z-2, Z-1 341 Type E-3, E-2, E-1, 341 ML, 341 N
Volvo	97305, 97307
MB	235.4
Eaton Europe	300,000 km or 3 years
API	GL-4
Military	MIL-L-2105



TECHNICAL DATA SHEET

Typical Test Data:

Specific Gravity @ 15°C	0.859
Kinematic Viscosity @ 100°C (cSt)	9.60
Kinematic Viscosity @ 40°C (cSt)	56.4
Viscosity Index	155
Flash Point COC (°C)	215
Pour Point (°C)	-39

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.