



TECHNICAL DATA SHEET

75W-80 HD GL5

Semi-synthetic based GL-4 & GL-5 gear oil

Product code: U311

Product Description:

75W-80 HD is a semi-synthetic universal extreme pressure gear oil meeting the API performance levels GL-4 & GL-5. 75W-80 HD is manufactured from high quality base oils and high levels of extreme pressure (EP) additives to provide a lubricant with outstanding anti-wear protection. It is designed to cope with the increasing demands of today's motoring conditions, which include high shock & load, high torque, and high speed service conditions.

Benefits:

- Semi-synthetic formulation
- Excellent oxidation stability
- Outstanding low and high temperature performance
- Suitable for synchromesh gearboxes
- Long service life
- High level of wear protection

Application:

75W-80 HD is suitable for manual gearboxes, including synchromesh, fitted to automotive vehicles, industrial and commercial vehicles.

Product Specification:

API	GL-4 & GL-5
-----	-------------

75W-80 HD is also recommended where the specification MTF-94 is called for.

Typical Test Data:

Specific Gravity @ 15.6°C	0.872
Kinematic Viscosity @ 100°C (cSt)	8.8
Kinematic Viscosity @ 40°C (cSt)	55.9
VI	134
Flash Point COC (°C)	217
Pour Point (°C)	-44

Health & Safety:

Please refer to the health and safety data sheet, a copy of which is freely available to all of our customers.