



TECHNICAL DATA SHEET

AUTO-TRANS CVT

Fully synthetic continuously variable transmission fluid

Product code: U316

Product Description:

Auto-Trans CVT is a high performance, fully synthetic transmission fluid designed to provide optimum performance in a wide range of continuously variable transmission (CVT) equipped passenger vehicles. The specialised performance additive package incorporated into Auto-Trans CVT has demonstrated equal, and in many cases better, performance than most OEM supplied fluids in areas such as metal to metal wear protection of belt elements and pulleys.

Benefits:

- Exceptional shear stability
- Low temperature fluidity
- Low foaming
- Excellent oxidation resistance
- Anti-shudder durability
- Excellent wear protection

Typical Test Data:

Appearance	Red fluid
Kinematic Viscosity @ 100°C (cSt)	7.20
Kinematic Viscosity @ 40°C (cSt)	33.7
Viscosity Index	185
Flash Point COC (°C)	200
Pour Point (°C)	-48
Brookfield Viscosity @ -40°C (cP)	9020

Application:

Auto-Trans CVT is recommended for a use in a wide range of passenger car vehicles fitted with continuously variable transmissions. In particular, Auto-trans CVT can be used where any of the following specifications / OEM fluids is required. **Auto-Trans CVT should NOT be used in conventional stepped automatic transmissions, DCT (Dual Clutch Transmissions), manual transmissions or Toyota e-CVT (THS, Toyota Hybrid System).**



TECHNICAL DATA SHEET

Product Specification:

Audi / VW	G 052 516, TL 52180, G 052 180 A1/A2/A6
Ford	CFT30, WSS-M2C933-A, Mercon C, CFT23
Honda	HMMF, HCF-2
Toyota / Lexus	TC
Nissan	NS-1, NS-2
Mitsubishi	CVTF-J1
Mazda	CVTF 3320
Subaru	i-CVTF, Lineartronic CVTF, K0425Y0710, CV-30, e-CVTF
Mini Cooper	EZL 799, EZL 799A, ZF CVT V1
Hyundai / Kia	SP-CVT 1
Suzuki	CVTF 3320, TC, NS-2, CVT Green 1
Dodge / Jeep	NS-2 , CVTF+4, MOPAR CVT 4
GM /Saturn	DEX-CVT
Mercedes-Benz	236.20, CVT 28
Renault	ELFMATIC
BMW	8322 0 136 376, 8322 0 429 154 (EZL799, EZL 799A)

Auto-Trans CVT is also suitable for use out of warranty where the following low viscosity fluids were specified:

Nissan	NS-3
GM / Saturn	CVTF I-Green2
Mitsubishi	Mitsubishi CVTF-J4
Suzuki	CVTF Green 2
Toyota / Lexus	FE

Health & Safety:

Please refer to the health and safety data sheet, a copy of which is freely available to all of our customers