



TECHNICAL DATA SHEET

AUTO-TRANS D VI

Fully synthetic automatic transmission fluid

Product code: U320

Product Description:

Auto-Trans D VI is a premium quality, fully synthetic automatic transmission fluid and is formulated primarily for applications requiring GM's Dexron VI specification.

Auto-Trans D VI features many advantages over more traditional automatic transmission fluids such as improved shear stability, excellent wear control and extended fluid life.

Benefits:

- Extended fluid life
- Primarily designed for GM DEXRON VI applications
- Fuel economy benefits
- Improved low temperature performance
- Backwards compatible with previous Dexron grades including Dexron IIIH, IIIG & IID.
- Improved frictional properties
- Outstanding wear protection
- High film strength
- Low foaming

Typical Test Data:

Appearance	Red fluid
Density @ 15.6°C	0.845
Kinematic Viscosity @ 100°C (cSt)	6.00
Brookfield Viscosity @ -40°C (cP)	12,030
Flash Point PMCC (°C)	190
Pour Point (°C)	-53

Applications:

Auto-Trans DVI is recommended for step type automatic transmissions and power steering units in cars, vans, trucks, buses and agricultural and industrial machines where the following specifications are required.



TECHNICAL DATA SHEET

Product Specification:

GM	Dexron VI, Dexron IIIH, IIIG, IID, TASA
JASO	1A
Allison	C-4
Caterpillar	TO-2
Mercedes-Benz	236.5
Voith	55.6335 (formerly G607)
Volvo	97340
ZF	TE-ML 09

In addition, Auto-Trans DVI is recommended for service fill in the following applications or where the following OEM genuine oils were originally required.

AISIN WARNER JWS 3309, JWS 3324, T IV	FIAT (ALL VEHICLES), TYPO T IV	SAAB T IV (JWS 3309)
AS 68 RC (T IV)	HONDA / ACURA Z-1, PREMIUM	SATURN T IV (JWS 3309)
AUDI 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)	HYUNDAI/ KIA SP II, SP III, SP IV & HYUNDAI SPH-IV	SCION (ALL VEHICLES)
AUDI 5 HP LT 71141 (AUDI G-052-162-A1 / A2)	NISSAN / INFINITY MATIC D, MATIC J, MATIC K, MATIC S	SHELL M 115
AUDI 5 HP (ZF 5 HP 30)	ISUZU BESCO ATF II, ATF III	SUBARU ATF, ATF HP
AUDI G-055-025-A2 (JWS 3309)	JAGUAR ATF 3403 M115, LT 71141, JLM 20238	SUZUKI ATF 3309
BMW ETL-7045, 7045E	JWS 3309 (T IV)	TEXACO ETL-7045E
BMW LA2634	JWS 3324 (WS)	TEXACO ETL-8072B
BMW 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)	MAZDA ATF M III	TOYOTA TYPE T-III, T-IV (JWS 3309)
BMW 5 HP (ZF 5 HP 30)	MERCEDES BENZ ZF HP20, 236.1, 236.5, 236.6, 236.7, 236.8, 236.9	TOYOTA WS (JWS 3324)
BMW ETL-8072B	MITSUBISHI DIAMOND SP II, SP III, SP IV	VOLVO T IV (JWS 3309)
BMW MINI JWS 3309	NAG 1	VW 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)
CHRYSLER/DODGE MOPAR AS 68 RC (T IV)	OPEL (All Vehicles)	VW 5 HP LT 71141 (VW G-052-162-A1 / A2)
DAEWOO LT 71141	PEUGEOT ZF 4 HP20	VW 5 HP (ZF 5 HP 30)
ESSO LT 71141	PORSCHE ATF 3403-M115, LT 71141, T IV (JWS 3309)	VW G-055-025-A2 (JWS 3309)

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.