



TECHNICAL DATA SHEET

HD 75W-85

Fully synthetic gear oil

Product code: U329

Product Description:

HD 75W-85 is a fully synthetic gear oil manufactured from very high quality synthetic base stocks, highly effective extreme pressure and anti-wear additives and premium shear stable viscosity modifiers.

HD 75W-85 offers improved fuel saving benefits combined with unsurpassed load carrying capacity while the high thermal stability of the product's components allows extended oil drain intervals to be realised. The levels of protection provided ensure maximum component durability.

Benefits:

- Improved fuel saving properties
- Excellent low temperature fluidity
- Maximum component protection
- High levels of oxidation resistance
- Outstanding thermal stability

Applications:

HD 75W-85 is recommended for a variety of highly stressed manual gearboxes, heavily loaded axle drives and other transmission equipment found in many passenger cars and light duty commercial vehicle applications.

Product Specification:

API	GL-4, GL-5
-----	------------

Typical Test Data:

Appearance	Clear & Bright
Density @ 20°C	0.857
Kinematic Viscosity @ 40°C (cSt)	78.0
Kinematic Viscosity @ 100°C (cSt)	12.0
Viscosity Index	149
Brookfield Viscosity @ -40°C (cP)	75,000
Flash Point COC (°C)	215