



TECHNICAL DATA SHEET

MTF LV

Fully synthetic gear oil

Product code: U330

Product Description:

MTF LV is a fully synthetic ultra low viscosity manual transmission fluid that can be used in a wide variety of modern passenger cars and light duty commercial vehicles. It is formulated using carefully selected synthetic basestocks and specialised advanced additives designed to protect transmission systems and offer the best possible fuel economy in all driving conditions.

Benefits:

- Exceptional low temperature fluidity
- Excellent fuel economy properties
- Outstanding oxidation stability
- Compatible with sensitive materials

Applications:

MTF LV is recommended for use in manual transmissions where an ultra low viscosity fluid is required by the vehicle manufacturer. It may also be used in some dry clutch DCT systems. In particular, MTF LV can be used where any of the following specifications or part numbers are required.

Product Specification:

API	GL-4
BMW	MTF LT-3
Fiat	9.55550-MZ6
Ford	M2C200-D2, M2C200-D3, M2C200-E1
GM	19259104, 19259105, 1940004
Nissan	Special Gear Oil Nissan LV MT-1
PSA	Special PSA Fluid Part No. 1618078480, Special PSA Gear Oil 9730 A8
VW	G 052 171, G 052 178, G 052 512, G 052 527, G 052 726, G 052 798, G 055 512, G 060 726

Typical Test Data:

Density @ 20°C	0.837
Kinematic Viscosity @ 100°C (cSt)	6.7
Kinematic Viscosity @ 40°C (cSt)	33.0
Viscosity Index	165
Pour Point (°C)	-51