



TECHNICAL DATA SHEET

75W FS GL4

Fully synthetic low viscosity manual transmission fluid

Product code: U334

Product Description:

75W FS GL4 is a fully synthetic low-viscosity manual transmission fluid that can be used in a wide variety of modern vehicles. It is formulated using carefully selected synthetic basestocks and specialised advanced additives, designed to protect transmission systems and offer the best possible fuel economy in all driving conditions.

Benefits:

- Multi-vehicle fluid specified by many manufacturers
- Excellent fuel economy properties
- Outstanding performance across a wide temperature range
- Long-lasting formulation, designed for maximum product life

Application:

75W FS GL4 is suitable for synchronised manual transmissions where a fluid of this type is specified by the vehicle manufacturer. It may also be used in some dry-clutch DCT systems where a fluid of this type is specified.

Product Specification:

| | |
|------|--|
| API | GL-4 |
| BMW | MTF LT-3 |
| Ford | M2C200D-2, M2C200D-3 |
| PSA | Special PSA fluid, part no. 1618078480 9730A8 |
| VW | G 052 178, G 052 512, G 052 527 G 052 726, G 060 726, G 070 726 |

Typical Test Data:

| | |
|-----------------------------------|-------|
| Density @ 20°C | 0.840 |
| Kinematic Viscosity @ 100°C (cSt) | 6.5 |
| Kinematic Viscosity @ 40°C (cSt) | 33.5 |
| Viscosity Index | 151 |
| Pour Point (°C) | -45 |