

## PREMIUM AGRI 10W-30

Mineral oil based super universal tractor oil Product code: U801

### Product Description:

Premium Agri 10W-30 is an advanced high performance universal oil designed for use in the latest agricultural machinery. It is also recommended for a number of other off-highway equipment including construction, demolition and excavation where any of the specifications below and a SAE 10W-30 viscosity grade are called for.

Premium Agri 10W-30 is formulated using highly refined mineral base stocks together with state of the art additives which provide the ultimate protection against wear and corrosion and help eliminate wet brake noise and chatter.

### **Benefits:**

- Exceptional wear protection
- Enhanced anti-squawk properties providing superior wet brake performance
- Improved low temperature stability
- Meets a variety of OEM requirements
- Suitable for a wide range of off highway machinery requirements
- High API diesel specification

### Applications:

Premium Agri 10W-30 is suitable for use in naturally aspirated and turbocharged diesel and petrol engines, transmissions, hydraulic systems, final drives, wet brakes and oil immersed clutches.

### **Product Specification:**

#### **STOU Specifications**

| Massey Ferguson | CMS M1145      |  |
|-----------------|----------------|--|
|                 | M1144          |  |
| John Deere      | J27            |  |
| Ford            | M2C159-B/C     |  |
| FNH             | 8200 9201      |  |
| New Holland     | NH 030C        |  |
| ZF              | TE-ML 03A      |  |
|                 | TE-ML 06B      |  |
|                 | TE-ML 07B, 07D |  |



# TECHNICAL DATA Sheet

### **UTTO Specifications**

| Massey Ferguson | CMS M1145 |
|-----------------|-----------|
|                 | M1143     |
| John Deere      | J20C      |
| Ford            | M2C134-D  |
|                 | M2C86-B   |
| New Holland     | NH 420A   |
|                 | NH 410B   |
| CaseNewHolland  | MAT 3525  |
|                 |           |

### **Gear & Transmission Specifications**

| API         | GL-4        |
|-------------|-------------|
| Allison     | C4          |
| Caterpillar | TO-2        |
| Afnor       | NFE 68603 E |

### **Engine Specifications**

| ACEA     | E3                    |
|----------|-----------------------|
| API      | CG-4, CF-4, CF, CE/SF |
| MB       | 227.1                 |
| CCMC     | D4                    |
| Military | MIL-L-2104D           |

### **Typical Test Data:**

| Specific Gravity @ 15.6°C         | 0.881 |
|-----------------------------------|-------|
| Kinematic Viscosity @ 100°C (cSt) | 9.70  |
| Kinematic Viscosity @ 40°C (cSt)  | 62.0  |
| Viscosity Index                   | 141   |
| Flash Point COC (°C)              | 223   |
| Pour Point (°C)                   | -38   |
| TBN (mg KOH / g)                  | 10.37 |

### Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.