



# TECHNICAL DATA SHEET

## AGRI 15W-30

Mineral oil based Super Universal Tractor Oil

Product codes: U802

### Product Description:

AGRI 15W-30 is a Super Universal Tractor Oil grade suitable for engines, transmissions, hydraulics and final drives.

The latest agricultural machinery in the modern intensive farming environment needs the protection of a high quality lubricant. AGRI 15W-30 is blended from carefully selected base oils and the latest in additive technology to produce a lubricant for the demands of most farm equipment. The latest additives used help reduce wet brake noise. The carefully selected base oils ensure protection even under the most arduous of conditions.

### Benefits:

- Meets a range of OEM requirements
- Helps reduce wet brake noise or “squawk”
- Suitable for many agricultural machinery requirements
- API diesel & petrol engine specifications

### Application:

AGRI 15W-30 is suitable for use in both normally aspirated and turbocharged diesel and petrol engines, transmission systems including those fitted with wet brakes, hydraulic systems, oil immersed clutches, gearboxes and final drives. It is suitable for agricultural, plant and off road machinery.

### Product Specification:

API	CE/SF (Engine), GL-4 (Gears)
CCMC	D4/G2
MB	227.1
Massey Ferguson	1135, 1127, 1139
Ford	M2C 86A, 134B/C, 159B
Allison	C4
John Deere	J20A
ZF	TE ML 06B, 06L, 07B, 07D
Caterpillar	TO-2



# TECHNICAL DATA SHEET

**Typical Test Data:**

Specific Gravity @ 15.6°C	0.883
Kinematic Viscosity @ 100°C (cSt)	11.49
Kinematic Viscosity @ 40°C (cSt)	85.04
Viscosity Index	125
Flash Point COC (°C)	218
Pour Point (°C)	-31
TBN (mg KOH / g)	10.38

**Health & Safety:**

Please refer to the safety data sheet, a copy of which is freely available to all of our customers