



TECHNICAL DATA SHEET

AGRI UTTO LV

Synthetic off-highway universal oil for transmissions, hydraulics, final drives and wet brakes

Product code: U806

Product Description:

AGRI UTTO LV is a fully synthetic, low viscosity universal tractor transmission oil designed to provide long drain performance in a wide variety of off-highway applications.

Benefits:

- Improved anti-squawk performance in brake systems
- Excellent oxidation stability
- Outstanding anti-wear protection
- Meets the very latest OEM requirements
- Excellent low temperature properties

Application:

AGRI UTTO LV is suitable for many modern tractor transmissions, hydraulics, final drives and wet brake systems. AGRI UTTO LV can also be used in older equipment and in particular where any of the following industry or OEM specifications are required.

Performance Specification:

API	GL-4
Volvo	WB 102 (97304), WB 101 (97303)
John Deere	J20D, J20C, J20B, J20A
Massey Ferguson	M1145, M1143, M1141, M1135
Case New Holland	MAT 3540, MAT 3526, MAT 3525, MAT 3505
Case	MS 1206, MS 1207, MS 1209, MS 1210
New Holland	NH 420A, NH 410B
ZF	TE-ML 03E, 05F, 06K, 17E, 21F
Kubota	Super UDT, UDT
Valtra	G2-08
Allison	C-4
Caterpillar	TO-2
Ford	M2C134-D, M2C86-B
Komatsu	AXO80

Typical Test Data:

Appearance	Clear and Bright
Density @ 15.6°C	0.858
Kinematic Viscosity @ 100°C (cSt)	7.80
Kinematic Viscosity @ 40°C (cSt)	39.8
Viscosity Index	171
Brookfield Viscosity @ -40°C (cP)	20,300
Flash Point COC (°C)	225
Pour Point (°C)	-48